

轮片特点

轮面材料:	超级聚氨酯	轮芯材料:	高强度聚丙烯
轴 承:	双滚珠	胎面硬度:	95A±3
建议温度:	-20°C~50°C	运行速度:	4km/h

注意: 超出建议温度范围或超出建议速度使用, 可能会缩短产品使用寿命甚至损坏产品。

- ✔ 不锈钢双轴, 防水、防锈, 转动灵活
- ✔ 注塑超级聚氨酯材质, 锁扣式注塑成型, 耐油, 耐磨
- ✔ 环保静音, 有效保护地面













运行省力	■ ■ ■ ■ □	良好
磨损寿命	■ ■ ■ ■ ■	优秀
静音效果	■ ■ ■ ■ □	良好
地面保护	■ ■ ■ ■ □	良好



支架特点


- ✔ 踩踏省力, 解刹方便
- ✔ 304不锈钢冲压成型, 防锈防腐
- ✔ 防尘圈有效保护油脂润滑, 避免灰尘等杂质进入
- ✔ 抛光处理, 光亮美观
- ✔ 镀锌处理, 盐雾测试满足48小时以上

外形尺寸 (mm)	 载重	 轮径	 轮宽	 全高	 偏心距 F	 旋转半径 r	 旋转半径 R
3"	110 kg	75	32	108	34	71.5	108.5
4"	140 kg	100	32	135	32	82	108.5
5"	150 kg	125	32	160	32	94.5	112.5




[中文简体]


安装尺寸



平底活动/刹车底板



平底固定底板



丝杆

产品代码

产品图片



轮径

平板万向

平板定向

平板刹车

丝杆万向

丝杆刹车

3"

20D01-1388

20D03-1388

20D02-1388

20D13-1388

20D14-1388

4"

20D07-1389

20D09-1389

20D08-1389

20D15-1389

20D16-1389

5"

20D10-1390

20D12-1390

20D11-1390

20D17-1390

20D18-1390

产品特征



电解抛光, 美观简洁

双轴承设计, 并配防尘盖



防尘圈保护, 有效防尘, 保护油脂润。

同款轮片

PUPBa

